



Special Molded DCPD Caustic Funnels and Interrupter Assemblies



DCPD Advantages

- Reaction-Injection Molded (RIM) as a *single piece*
 - Therefore, no weld failure occurs, which otherwise might happen with a welded PP funnel.
 - High-Temperature and Corrosion-Resistant
 - Highly Durable Thermoset Plastic
 - Highly electrically-insulating
 - Service Temperature: -40 to +110°C (-40 to +230°F)

Serving the Chemical Industry Worldwide | www.princecorp.com



Special Molded DCPD Caustic Funnels and Interrupter Assemblies

Part Number Format: PP-_____, given in red text

Parts	Hooker-Style	Diamond-Style	
DCPD Molded Funnels			
Photos			
Neck Sizes Available	<p>2" (1284-H2M) 3" (1285-H3M)</p>	<p>3" (1286-H3M) *Reducer bushing, sold separately, is available to fit into 2" caustic pipe stub</p>	
Notes	More tall, slender, and ovular (top-view) shape	Wider, more circular (top-view) shape allows for less precise percolation pipe location	
Interrupter Support Plate: P-72 Styrene Copolymer or High-Temperature PP			
Photos	<p>5 – 11/16" Diameter (144 mm)</p>		
Details	<p>P72F9134-950688</p> <ul style="list-style-type: none"> P-72 Styrene Copolymer Interrupter Support Plate with Cut Corners and a Center Hole <p>PPF9134-950688</p> <ul style="list-style-type: none"> High-Temperature PP Interrupter Support Plate with Cut Corners and a Center Hole 	<p>* Interrupter Support Plate is not Required for Diamond-Style Funnels</p>	
Molded Interrupter Cups DCPD or High-Temperature PP			
Photos			
Interrupter Cup Details	<p>1287-ICM</p> <ul style="list-style-type: none"> 42 ea, 1/4" Ø bottom holes (6.4 mm) <p>1289-ICM</p> <ul style="list-style-type: none"> 42 ea, 3/16" Ø bottom holes (4.8 mm) 	<p>1288HM-__: compatible for BOTH Hooker and Diamond-Style Funnels</p> <p>3: with 144 bottom holes x 3/16" Ø (4.8mm) 4: with 144 bottom holes x 1/4" Ø (6.4 mm)</p> <p>R-3: Molded in 1" High Riser, with 144 bottom holes x 3/16" Ø (4.8 mm) R-4: Molded in 1" High Riser, with 144 bottom holes x 1/4" Ø (6.4 mm)</p>	<p>1287-ICM-D</p> <ul style="list-style-type: none"> 42 ea, 1/4" Ø bottom holes (6.4 mm), with cutout for perc. pipe and 2 ea. 1/4" Ø holes for hanger <p>1289-ICM-D</p> <ul style="list-style-type: none"> 42 ea, 3/16" Ø bottom holes (4.8 mm), with cutout for perc. pipe and 2 ea. 1/4" Ø holes for hanger



Special Molded DCPD Caustic Funnels and Interrupter Assemblies

Demister Pads

Pad of Woven Polypropylene Strands, for placement in the bottom of the Caustic Interrupter Cup to retard splash and assist in breakup of Caustic droplets.

***Available in 2 Sizes:**

Prince PPRO-7-329

5" wide x 7-5/8" long (oblong) x 2-1/2" high (127 x 194 x 64 mm)

Prince PPRO-SSOO-2500

5-1/2" Diameter (round) X 2-1/2" high (140 x 64 mm)



Adapter Bushings

Optional Adapter Bushings of EPDM Elastomer to assist seating Funnels in Caustic Outlet Stand Pipes.

Part No. (-)	Pipe Size	Bushing Dia.
-1	2-1/2" Sch 40	2 ³ / ₈ " (60.3 mm)
-2	2-1/2" Sch 80	2 ¹ / ₄ " (57.2 mm)
-3	3" Sch 40	2 ³¹ / ₃₂ " (75.4 mm)
-4	3" Sch 80	2 ¹³ / ₁₆ " (71.4 mm)



Caustic Funnel Assembly

